

Physical parameters	
Weight кg/lbs	155 kg / 342 lbs
Dimensions mm/inch	500 × 1120 × 825 mm 19.7 × 44.1 × 32.5"

Field of application

The floor scraper with its different blades is extremely useful for:

- Strip floor coverings
- Lift carpet tiles and foam backed carpets
- Remove felt, underlay
- Linoleum and vinyl flooring
- Cork tiles and matting
- Ceramic and granite tiles

The machine works off screed, latex, concrete or wood surfaces and will lift floor coverings leaving a minimum of residue and backing. It can also be used to create a distressed effect on hardwood flooring.

SC 25 Floor scraper

Article code	Power	Consumption
800074	230 V / 50 Hz	10.9 A
800081	115 V / 50 Hz	22.4 A
800082	115 V / 60 Hz	22.2 A

Key features	
Working width	250 - 270 mm / 9.8 - 10.6"
Distance to wall	110 mm / 4.3" (basic blade)
El. motor size	90 L
Power	1.5 kW
Motor speed	2800 RPM
Machine speed	10.6 m (34") / min
Motor protection switch	25 A / 115 V, 13.5 A / 230 V
Sound pressure level	≤ 90.5 db(A)
Acoustic power level	≤ 98.0 db(A)
Vibration level	8.8 m/s2
Protection type	IP 55

Spare parts

Basic blade 400123	250×80×1.5 mm 9.8×3.1×0.06"	Application: • Strip floor coverings • Lift carpet tiles and foam backed carpets • Cork tiles and matting
Long blade 400238	250×130×1.5 mm 9.8×5.1×0.06"	 Application: Strip floor coverings Lift carpet tiles and foam backed carpets Cork tiles and matting
U-blade 400213	270×80×1.5 mm 10.6×3.1×0.06"	Application:Remove felt, underlayLinoleum and vinyl flooringMatting
Debris blade 400217	200×80×2.5 mm 7.9×3.1×0.1"	Application:Hard glued floor coveringsDebris
Basic blade 400110 (Optional)	200×100×1.5 mm 7.9×3.9×0.06"	 Application: Strip floor coverings Lift carpet tiles and foam backed carpets Cork tiles and matting
U-Blade 400215 (Optional)	230×100×2 mm 9.1×3.9×0.08"	Application: Remove felt, underlay Linoleum and vinyl flooring Matting
Chisel set 400253 (Optional)	Chisel holder Chisel: 25×280 mm / 0.98×11" Chisel: 50×300 mm /1.98×11.8"	Application: • Tiles • Parquet • Hard debris